

What is claimed is:

1. A reflecting device having electrically controllable, variable reflection,
comprising:

a composition comprising a periodic array of liquid crystal disposed in a
5 polymer matrix, the liquid crystal having an index of refraction that is variable in
response to an applied electric field, wherein the index of refraction of the liquid
crystal array and the index of refraction of the polymer matrix, n_p , are mismatched at
said first and second applied electric field strength; and

a pair of electrodes positioned to apply an electric field across the composition
10 and capable of applying the first and second applied electric field strengths.

2. The reflecting device of claim 1, wherein the first applied electric field
strength is zero.

15 3. The reflecting device of claim 1 or 2, wherein the second applied electric
field strength is sufficient to substantially align the liquid crystal droplets.

4. The reflecting device of claim 1, wherein the device possesses at least two
reflection wavelengths, each reflection wavelength associated with a different applied
20 field strength.

5. The reflecting device of claim 1, wherein the liquid crystal has an ordinary index of refraction, n_o , and an extraordinary index of refraction, n_e , and the polymer has a refractive index, n_p , and where $n_o \neq n_p$.

5 6. The reflecting device of claim 1, wherein the liquid crystal has an ordinary index of refraction, n_o , and an extraordinary index of refraction, n_e , and the polymer has a refractive index, n_p , and where $n_e > n_p > n_o$.

10 7. The reflecting device of claim 1, wherein the liquid crystal has a positive dielectric anisotropy.

8. The reflecting device of claim 1, wherein the liquid crystal has a negative dielectric anisotropy.

15 9. The reflecting device of claim 1, wherein the liquid crystal has a dielectric anisotropy dependent upon applied field frequency.

20 10. The reflecting device of claim 1, wherein the device is selected from the group consisting of waveguide gratings, switchable lenses, switchable filters, optical add-drop multiplexers and attenuators.

11. The reflecting device of claim 1, further comprising:

a power source in electrical communication with the electrodes for generating the electric field.

5 12. The reflecting device of claim 1, wherein the electrode comprises a conductive layer in electrical communication with the composition.

13. The reflecting device of claim 12, wherein the conductive layer comprises indium titanium oxide (ITO).

14. The reflecting device of claim 1, wherein the electrode comprises a metallic electrode.

15 15. A reflecting device having electrically controllable, variable reflection, comprising:

first and second electrodes having a holographic polymer dispersed liquid crystal (H-PDLC) film disposed therebetween, the H-PDLC film comprised of layers of liquid crystal and polymer matrix, the liquid crystal layer having a first average index of refraction, $\langle n_{LC} \rangle_1$, at a first applied electric field strength and a second average index of refraction, $\langle n_{LC} \rangle_2$, at a second applied electric field strength, wherein

20

the $\langle n_{LC} \rangle$'s of the liquid crystal and the index of refraction of the polymer matrix, n_p , are mismatched at both the first and second applied electric field strengths.

16. The reflecting device of claim 15, wherein the first applied electric field strength is zero.

17. The reflecting device of claim 15 or 16, wherein the second applied electric field strength is sufficient to substantially align the liquid crystal droplets.

18. The reflecting device of claim 15, wherein the liquid crystal further comprises a third $\langle n_{LC} \rangle$ substantially equal to n_p at a third applied electric field strength.

19. The reflecting device of claim 15, wherein the device possesses at least two reflection wavelengths, each reflection wavelength associated with a different applied field strength.

20. The reflecting device of claim 15, wherein the device possesses at least three different color states, each color state associated with a different applied field strength.

21. The reflecting device of claim 15, wherein the index mismatching conditions results in a shift in the bandwidth of reflected light, as the device liquid crystal moves from a state having a $\langle n_{LC} \rangle_1$ to a state having a $\langle n_{LC} \rangle_2$.

5 22. The reflecting device of claim 15, wherein the liquid crystal has an ordinary index of refraction, n_o , and an extraordinary index of refraction, n_e , and the polymer has a refractive index, n_p , and where $n_o \neq n_p$.

10 23. The reflecting device of claim 15, wherein the liquid crystal has a positive dielectric anisotropy.

15 24. The reflecting device of claim 15, wherein the liquid crystal has a negative dielectric anisotropy.

20 25. The reflecting device of claim 15, wherein the liquid crystal has a dielectric anisotropy dependent upon applied field frequency.

25 26. The reflecting device of claim 15, wherein the device is selected from the group consisting of waveguide gratings, switchable lenses, switchable filters, optical add-drop multiplexers and attenuators.

27. The reflecting device of claim 15, further comprising:

a power source in electrical communication with the electrodes for generating the electric field.

5 28. The reflecting device of claim 15, wherein the electrode comprises a conductive layer in electrical communication with the composition.

29. The reflecting device of claim 28, wherein the conductive layer comprises indium titanium oxide (ITO).

10 30. The reflecting device of claim 15, wherein the electrode comprises a metallic electrode.

31. A grating having electrically controllable, variable peak wavelength,
15 comprising:

a periodic array of diffractive planes in a supporting matrix, said planes forming a grating spaced at a distance on the order of a wavelength of light and having an optical thickness responsive to an applied electric field;

first and second electrodes for applying first and second applied electric field
20 strengths across the grating,

wherein the first and second electric field strengths alter optical thickness to alter peak wavelength of reflected light.

32. A reflecting device having electrically controllable, variable reflection,

5 comprising:

a periodic array of liquid crystals disposed in a polymer matrix, the liquid crystal having an index of refraction variable in response to an applied electric field; and

means for applying an electric field across the device to provide first and
10 second applied electric field strengths,

wherein index of refraction of the liquid crystal and the index of refraction of the polymer matrix, n_p , are mismatched at said first and second applied electric field strengths.

15 33. A method of varying the optical thickness of a reflecting device, comprising:

providing a reflecting device comprising a periodic array of liquid crystal in a polymer matrix, the liquid crystal array having an index of refraction variable in response to an applied electric field; and

20 altering the electric field strength across the H-PDLC film between the first and second applied electrical field strengths, wherein the indices of refraction of the

liquid crystal are mismatched with the index of refraction of the polymer matrix at both the first and second applied electrical field strengths.

34. The method of claim 33, wherein the reflecting device comprises first
5 and second substrates having a holographic polymer dispersed liquid crystal (H-PDLC) film disposed therebetween, the H-PDLC film comprised of layers of liquid crystal and polymer matrix.

35. The method of claim 33, wherein the liquid crystal has an ordinary index
10 of refraction, n_o , and an extraordinary index of refraction, n_e , and the polymer has a refractive index, n_p , and where $n_o \neq n_p$.

36. The method of claim 33, wherein the peak wavelength of the reflected
light shifts as the liquid crystal moves from a state having a first average index of
15 refraction at the first applied electric field strength to a state having a second average index of refraction at the second applied electric field strength.

37. The method of claim 33, wherein the device exhibits a continuum of
reflection wavelengths as the applied field strength is varied between the first and
20 second applied field strengths.

38. The method of claim 33, wherein the reflection wavelength shifts to lower wavelength as the field strength is increased.

39. The method of claim 37, wherein the reflection wavelength shifts to higher wavelength as the field strength is increased.

40. The method of claim 33, wherein the bandwidth of reflected light varies as the applied field strength is varied between the first and second applied field strengths.

41. The method of claim 33, wherein the applied field strength is of sufficient strength to align the liquid crystal droplets to an extent sufficient to alter the LC index of refraction.

42. The method of claim 33 or 41, wherein the first applied electric field strength is zero.

43. The method of claim 33 or 41, wherein the applied electric field strength is in the range of about 0V to 240 V.

44. The method of claim 33, wherein the liquid crystal further comprises a third average index of refraction substantially equal to the index of refraction of the polymer crystal.

5 45. A method of modifying reflection characteristics in an H-PDLC reflecting device, comprising:

providing a reflecting device comprising first and second substrates having a holographic polymer dispersed liquid crystal (H-PDLC) film disposed therebetween, the H-PDLC film comprised of layers of liquid crystal and polymer matrix, the liquid crystal having an average index of refraction, n_{LC} , and the polymer having an index of refraction, n_p ; and

altering the electric field strength across the H-PDLC film to vary the index of refraction of the liquid crystal such that the H-PDLC film moves from a first index mismatch condition to a second index mismatch condition, each said index mismatch condition associated with a characteristic reflection characteristic of the H-PDLC film.

46. The method of claim 45, wherein the step of moving from a first index mismatch condition to a second index mismatch condition comprises moving through a index matching condition.

47. A method of electrically controlling a variable peak wavelength of a grating, comprising:

a periodic array of diffractive planes in a supporting matrix, said planes forming a grating spaced at a distance on the order of a wavelength of light and

5 having an optical index responsive to an applied electric field; and

applying first and second applied electric field strengths to alter the peak wavelength of the grating.